

Carsington Plus Sports Floodlight





















READ THESE INSTRUCTIONS THOROUGHLY BEFORE **INSTALLATION KEEP THESE INSTRUCTIONS FOR FUTURE REFERENCE.**

IMPORTANT:

This product must be installed by a qualified electrician or competent person, and in accordance with current building and IET wiring regulations.

BOX CONTENTS

This lighting fixture has been properly packed to avoid damage during transit. Before commencing with the installation carefully inspect the luminaire to confirm there is no damage. DO NOT INSTALL if any damage has occurred to the fixture or any of its components:

- Light Fitting
- Instruction Manual
- Driver (Purchased separately)

TOOLS REQUIRED



36mm Spanner



Screwdriver



 Hex key 6mm & 8mm

INSTALLATION INSTRUCTIONS


Installation must be conducted by a qualified electrician. The Carsington has a variety of installation methods. See below:

Angle of elevation 25 degree




Horizontal installation






25 degrees Hoisting



(Vertical Hoisting)



Carsington Plus Control Gear

960W

Part No: 430512 100V - 277V



960W

Part No: 430526

390V - 415V



1650W

Part No: 430514

100V - 277V




1650W

Part No: 430527

390V - 415V



Quick connectors for portable Control Gear



- 1. For wiring the driver to the light, an additional H07RN-F will be required. (not supplied)
- 2. Remote installation of control gear: Extend M1, M2 and M3 depending on wattage
- 3. Use IP68 connectors supplied with control gear

PLEASE READ THESE INSTRUCTIONS **BEFORE INSTALLATION.**



WARNING: Risk of electric shock! Isolate the mains power before proceeding.

- Turn off the mains power before performing inspections, installation
- Verify that the supply voltage is correct by comparing it with the luminaire label information
- It is the installers responsibility to ensure installation is suitable for the total load of the luminaire(s). The supply cable, fuses/circuit brakers must be correctly rated for the electrical load and considering for any transient inrush currents that may occur
- Do not perform insulation strength or resistance tests on installed luminarie(s) connected





Right Side of Driver Box

AC Input 100-277V/AC

ACINDUI 100-277V/AC 50-60Hr



Carsington Plus Sports Floodlight



DISPOSAL

The light source of this unit is not replaceable; when the light source reaches its end of life the whole luminaire shall be replaced.

Disposal of Electronic Equipment WEEE Directive 2002/96/EC This product falls within the scope of the Waste Electrical & Electronic Equipment Directive (WEEE), which means the product should not be disposed of as normal household waste. Please recycle where facilities exist or check with your Local Authority.

ROHS - All components and materials used in this product are

Specifications may change from time to time. The information contained in this leaflet is for guidance only and should not be considered as always accurate and should be treated as not representative.

RoHS 2002/95/EC compliant.


WARRANTY

This luminaire is warranted for a period of 5 years from the date of purchase. The backup battery pack in the emergency version is warranted for a period of 12 or 24 months*. The warranty could be invalidated should the light fitting not be installed according to these instructions, outside the scope of the specification or the product has been altered or tampered with in any way. Please see website for terms and conditions.


OPERATING TEMPERATURE

Standard -20° to +45°C

	CARSINGTON PLUS SPORTS FLOODLIGHT DIMENSIONS					
Part No.	Description	Watts	L(mm)	W (mm)	H (mm)	
430510-25	Carsington Plus	600W	728	538	114	
430510-40	Carsington Plus	600W	728	538	114	
430510-60	Carsington Plus	600W	728	538	114	
430511-25	Carsington Plus	960W	580	656	138	
430513-25	Carsington Plus	1650W	791	673	138	



CARSINGTON PLUS CONTROL GEAR DIMENSIONS							
Part No.	Description	Watts	L(mm)	W (mm)	H (mm)		
430512	Carsington Plus Control Gear - 100V - 277V	960W	613	185	74		
430526	Carsington Plus Control Gear - 390V - 415V	960W	613	185	74		
430514	Carsington Plus Control Gear - 100V - 277V	1650W	628	185	119		
430527	Carsington Plus Control Gear - 390V - 415V	1650W	628	185	119		



CARSINGTON PLUS BACK SPILL PLATE INSTALLATION				
	M5 screws*4pcs			
	Unscrew the screws 4mm Hex Key			
	M5 22mm stainless steel inner hexagon screw - 4pcs M5 stainless steel washers - 4pcs Light barrier 1pc Fix light barrier lighten M5*22mm screws and washer 4mm Hex Key			
	Complete installation of light barrier			

^{*} Please see our website for more detailed information.

Technical Helpline: +44 (0)1507 328031